

ASROCK Main Board Desktop H510M-HDV (H510, S1200, 2xDDR4, 1xPCIe 4.0x16, 1xPCIe 3.0x1, 4xSATA3, 4xUSB3.2 Gen1, VGA, DVI-D, HDMI, GLAN, mATX

Šifra: 134480
Kategorija proizvoda: Matične ploče
Proizvođač: ASRock

MpCena: 11.128,00 rsd.

cena za odloženo plaćanje i kupovinu na rate

Web Cena: 9.274,00 rsd.

cena za web porudžbine i avansno plaćanje



| | |
|---|--|
| Chipset: | Intel H510 |
| Supports Central Processor Unit: | Intel 10th Gen Processors Intel 11th Gen Processors |
| CPU Socket Standard: | Socket 1200 |
| Architecture Features: | Intel® Rapid Storage Technology enterprise Intel Turbo Boost Max Technology 3.0 |
| CPU Maximum Quantity Supports: | 1 |
| Memory Type: | DDR4 SDRAM |
| Memory Form Factor: | DIMM 288-pin |
| Memory Speed: | 2133MHz(PC3-17066) 2400MHz(PC4-19200) 2666MHz(PC4-21300) 2800MHz(PC4-22400) 2933MHz(PC4-23400) 3200MHz(PC4-25600) |
| Maximum Installable System Memory Storage Capacity: | 64 GB |
| Memory Slot Total Quantity: | 2 |
| Provides Error Checking Method: | non-ECC |
| Memory Features: | Two DDR Channels Unbuffered XMP 2.0 |
| Integrated: | |

Storage Controller:
Supports: Level 0, Level 1,
Level 10, Level 5
SATA III-600 (4)

| | |
|------------------------------|--|
| Video Controller Integrated: | yes |
| Video Chipset: | Intel Iris Xe Graphics |
| Audio Integrated: | yes |
| Device Location: | Integrated |
| Audio Chipset: | Realtek ALC887-VD2 |
| Audio Output Mode: | 7.1 Channel Surround |
| Compliant Audio Standards: | High Definition Audio |
| LAN Integrated: | yes |
| LAN Chipset: | Realtek RTL8111H |
| Data Link Protocol Supports: | Gigabit EthernetFast EthernetEthernet |
| PCI Express 4.0 x16: | 1 |
| PCI Express 3.0 x1: | 1 |
| DVI: | 1 (DVI-D) |
| HDMI: | 1 (HDMI (Type A)) |
| VGA: | 1 (15-pin D-sub) |
| USB 3.2 Gen 1: | 2 (USB 3.2 (type A)) |
| USB 2.0: | 4 (USB 2.0 (type A)) |

Uvek smo ovde i tako već 20 godina!